October 2020 Newsletter



A manufacturer's representative with over 30 years experience serving the OEM lighting market.

Visit our website to learn more about the premier manufacturers we represent <u>oemlightingsales.com</u>



Outdoor Ingress Protection (OIP) option is IP66 rated!

This upgrade is significant for using the Vertex sensor in Wet Location fixtures because it has an IP66 rating when installed in a waterproof outdoor fixture.



Click here for the data sheet to learn more!



New Lithonia Lighting® LEM Series Emergency Drivers deliver essential Life Safety functionality for most Class 2 LED luminaire designs.

The LEM04 and LEM08 emergency drivers are effective emergency drivers that deliver up to 4W or 8W initial power to operate 20-50VDC LEDs for the coderequired 90 minutes.

The LEM04 and LEM08 are UL 924 Listed for field installation in United States and Canada and are available with metal conduit ("A" option) for external mounting on the luminaire or without metal conduit ("B" option) for integral installation within the channel space.

Lithonia Lighting LEM Series emergency drivers are practical options for meeting basic emergency lighting requirements for most standard fixtures and mounting heights.

Product Detail Pages:

LEM04 Emergency Drivers : Spec Sheet

LEM08 Emergency Drivers : Spec Sheet



The DTL product line is the leader in high-quality, cost-effective electronic outdoor photocontrols. Energy efficient and exceptionally reliable, DTL products are designed for a variety of applications including roadway, area lighting, floodlights, security and residential.

The DTL family now includes networked wireless photocontrols for long-life LED applications that create a foundation network canopy for smart cities.

Click <u>here</u> for our product catalog.

Please forward quote requests and orders to: orders@oemlightingsales.com

Visit our website to learn more about our premier manufacturers: www.oemlightingsales.com

Give us a call today! 718.321.0002

41-07 162nd St Flushing, NY 11358